



## TPA 500000 - THREE-PHASE TRANSFORMER 400/400V - 500KVA - IP00



SKU: 33601  
Référence technique: S37B60FF00000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 500 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : standard  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1960 W  
Load losses : 6400 W  
Voltage drop : 1,3 %  
UCC : 5 %  
Efficiency : 98,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 950 x 680 x 800 mm  
Mounting centres (a x b) : 600 x 420 mm  
Mounting diameter (ø) : 14 mm  
Weight : 1270 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 800A  
:  
Secondary 400V (gG fuse(s)) : 4 x 800A  
Secondary 400V (C circuit breaker(s)) : 4 x 800A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels