





TPA 5000 - ON REQUEST THREE-PHASE TRANSFORMER 5KVA - IP00



SKU: TPA5000_Specific
Référence technique: T28B40...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : Transformer (specific)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 85 W
Load losses : 210 W
Voltage drop : 4 %
UCC : 4,1 %
Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 200 x 310 mm
Mounting centres (a x b) : 250 x 130 mm
Mounting diameter (Ø) : 11x22 mm
Weight : 40 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization