






TPA 6300 - ON REQUEST THREE-PHASE TRANSFORMER 6,3KVA - IP00



SKU: TPA6300_Specific
 Référence technique: T28B41...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 6,3 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : Transformer (specific)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 95 W
 Load losses : 300 W
 Voltage drop : 4,5 %
 UCC : 4,7 %
 Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 200 x 360 mm
 Mounting centres (a x b) : 330 x 130 mm
 Mounting diameter (∅) : 11x22 mm
 Weight : 47 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization