






**TPA 8000 - THREE-PHASE
 TRANSFORMER 400/400V ±5% -
 ELECTROSTATIC SHIELD - 8KVA - IP00**



SKU: 33424
 Référence technique: A37B42FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 8 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : Transformer (electrostatic shield & regulation tabs ±5%)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 100 W
 Load losses : 485 W
 Voltage drop : 5,7 %
 UCC : 6,1 %
 Efficiency : 93,2 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 265 x 350 mm
 Mounting centres (a x b) : 330 x 235 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 52 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 12A
 :
 Secondary 400V (gG fuse(s)) : 4 x 12A
 Secondary 400V (C circuit breaker(s)) : 4 x 12A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels