




**TPA 8000 - THREE-PHASE
TRANSFORMER 400/230V $\pm 5\%$ -
ELECTROSTATIC SHIELD - 8KVA - IP00**



SKU: 34424
Référence technique: A37B42FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 8 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 100 W
Load losses : 485 W
Voltage drop : 5,7 %
UCC : 6,1 %
Efficiency : 93,2 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 265 x 350 mm
Mounting centres (a x b) : 330 x 235 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 52 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 12A
:
Secondary 230V (gG fuse(s)) : 4 x 20A
Secondary 230V (C circuit breaker(s)) : 4 x 20A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels