





TPA 80000 - THREE-PHASE TRANSFORMER 400/400V - 80KVA - IP00



SKU: 33521
Référence technique: A37B52FF00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 80 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 560 W
Load losses : 1960 W
Voltage drop : 2,4 %
UCC : 3,4 %
Efficiency : 96,9 %

DIMENSIONS:

Dimensions (A x B x H) : 600 x 370 x 610 mm
Mounting centres (a x b) : 470 x 340 mm
Mounting diameter (ø) : 11x22 mm
Weight : 280 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 125A
:
Secondary 400V (gG fuse(s)) : 4 x 125A
Secondary 400V (C circuit breaker(s)) : 4 x 125A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels