




## TPA 80000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - ELECTROSTATIC SHIELD - 80KVA - IP00



SKU: 33524  
Référence technique: A37B52FFF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 80 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 560 W  
Load losses : 1960 W  
Voltage drop : 2,4 %  
UCC : 3,4 %  
Efficiency : 96,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 600 x 370 x 610 mm  
Mounting centres (a x b) : 470 x 340 mm  
Mounting diameter ( $\emptyset$ ) : 11x22 mm  
Weight : 280 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 125A  
:  
Secondary 400V (gG fuse(s)) : 4 x 125A  
Secondary 400V (C circuit breaker(s)) : 4 x 125A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels