





TPAE 54 10000 - TTHREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/400V - 10KVA - IP54



SKU: 37431
Référence technique: A39B43...FF00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 10 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP54-IK08
Version : Transformer (standard)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 105 W
Load losses : 355 W
Voltage drop : 3,4 %
UCC : 3,7 %
Efficiency : 95,6 %

DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm
Mounting centres (a x b) : 330 x 430 mm
Mounting diameter (Ø) : 11x22 mm
Weight : 91 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 400V (gG fuse(s)) : 4 x 16A
Secondary 400V (C circuit breaker(s)) : 4 x 16A

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections

Specific colour for the enclosure