




TPAE 54 10000 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 10KVA - IP54



SKU: TP AE5410000_Specific
 Référence technique: A39B43.....

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 10 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP54-IK08
 Version : Transformer (specific)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 105 W
 Load losses : 355 W
 Voltage drop : 3,4 %
 UCC : 3,7 %
 Efficiency : 95,6 %

DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm
 Mounting centres (a x b) : 330 x 430 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 91 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure