




TPAE 54 200000 - THREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/230V - 200KVA - IP54



SKU: 38561
Référence technique: S39B56...FD00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 200 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP54-IK08
Version : Transformer (specific)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 1160 W
Load losses : 2790 W
Voltage drop : 1,4 %
UCC : 4,4 %
Efficiency : 98,1 %

DIMENSIONS:

Dimensions (A x B x H) : 1200 x 1070 x 1380 mm
Mounting centres (a x b) : 820 x 1020 mm
Mounting diameter (Ø) : 15 mm
Weight : 840 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 315A
:
Secondary 230V (gG fuse(s)) : 4 x 500A
Secondary 230V (C circuit breaker(s)) : 4 x 500A

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections

Specific colour for the enclosure