



## TPAE 54 400000 - THREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/230V - 400KVA - IP54



SKU: 38591  
Référence technique: S39B59...FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 400 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP54-IK08  
Version : Transformer (standard)  
Inrush current : less than or equal to 12 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 2075 W  
Load losses : 4740 W  
Voltage drop : 1,2 %  
UCC : 4,2 %  
Efficiency : 98,3 %

### DIMENSIONS:

Dimensions (A x B x H) : 1350 x 1200 x 1450 mm  
Mounting centres (a x b) : 920 x 1150 mm  
Mounting diameter (ø) : 15 mm  
Weight : 1440 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 630A  
:  
Secondary 230V (gG fuse(s)) : 4 x 100A  
Secondary 230V (C circuit breaker(s)) : 4 x 100A

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections

Specific colour for the enclosure