



TPAE 54 40000 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 40KVA - IP54



SKU: TP AE5440000_Specific
Référence technique: A39B49.....



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 40 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP54-IK08
Version : Transformer (specific)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 300 W
Load losses : 645 W
Voltage drop : 1,6 %
UCC : 2,1 %
Efficiency : 97,7 %

DIMENSIONS:

Dimensions (A x B x H) : 650 x 630 x 1020 mm
Mounting centres (a x b) : 395 x 560 mm
Mounting diameter (ø) : 11x22 mm
Weight : 243 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure