




TPAE 54 500000 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 500KVA - IP54



SKU: TP AE54500000_Specific
Référence technique: S39B60.....

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 500 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP54-IK08
Version : Transformer (standard)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 2515 W
Load losses : 5330 W
Voltage drop : 1,1 %
UCC : 4,7 %
Efficiency : 98,5 %

DIMENSIONS:

Dimensions (A x B x H) : 1500 x 1400 x 1700 mm
Mounting centres (a x b) : 970 x 1350 mm
Mounting diameter (ø) : 15 mm
Weight : 2060 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure