



## TPAE 54 6300 - THREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/230V - 6,3KVA - IP54



SKU: 38411  
Référence technique: A39B41...FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 6,3 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP54-IK08  
Version : Transformer (standard)  
Inrush current : less than or equal to 12 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 85 W  
Load losses : 230 W  
Voltage drop : 3,5 %  
UCC : 3,8 %  
Efficiency : 95,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm  
Mounting centres (a x b) : 330 x 430 mm  
Mounting diameter (Ø) : 11x22 mm  
Weight : 74 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 10A  
:  
Secondary 230V (gG fuse(s)) : 4 x 16A  
Secondary 230V (C circuit breaker(s)) : 4 x 16A

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Specific colour for the enclosure