





## TPAE 54 8000 - THREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/230V - 8KVA - IP54



SKU: 38421  
 Référence technique: A39B42...FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 8 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP54-IK08  
 Version : Transformer (specific)  
 Inrush current : less than or equal to 12 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 95 W  
 Load losses : 335 W  
 Voltage drop : 4 %  
 UCC : 4,3 %  
 Efficiency : 94,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm  
 Mounting centres (a x b) : 330 x 430 mm  
 Mounting diameter (Ø) : 11x22 mm  
 Weight : 87 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 12A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 20A  
 Secondary 230V (C circuit breaker(s)) : 4 x 20A

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Vibration isolating mount  
 Rung wheels  
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure