



TPAE 65 10000 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 10KVA - IP65



SKU: TP AE6510000_Specific
Référence technique: A39B43...P.....



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 10 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP65-IK08
Version : Transformer (specific)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 105 W
Load losses : 355 W
Voltage drop : 3,4 %
UCC : 3,7 %
Efficiency : 95,6 %

DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm
Mounting centres (a x b) : 330 x 430 mm
Mounting diameter (ø) : 11x22 mm
Weight : 91 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Running wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure