




TPAE 65 125000 - THREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/400V - 125KVA - IP65



SKU: 37545
 Référence technique: S39B54...P...FF00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 125 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP65-IK08
 Version : Transformer (specific)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 1160 W
 Load losses : 1075 W
 Voltage drop : 1,5 %
 UCC : 2,3 %
 Efficiency : 97,9 %

DIMENSIONS:

Dimensions (A x B x H) : 1200 x 1070 x 1380 mm
 Mounting centres (a x b) : 820 x 1020 mm
 Mounting diameter (ø) : 15 mm
 Weight : 1095 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A
 :
 Secondary 400V (gG fuse(s)) : 4 x 200A
 Secondary 400V (C circuit breaker(s)) : 4 x 200A

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Rung wheels
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure