



TPAE 65 31500 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 31,5KVA - IP65



SKU: TP AE6531500_Specific
 Référence technique: A39B48...P.....

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 31,5 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP65-IK08
 Version : Transformer (standard)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 220 W
 Load losses : 595 W
 Voltage drop : 1,9 %
 UCC : 2,5 %
 Efficiency : 97,5 %

DIMENSIONS:

Dimensions (A x B x H) : 650 x 630 x 1020 mm
 Mounting centres (a x b) : 395 x 560 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 211 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure