





## TPAE 65 6300 - ON REQUEST THREE-PHASE DUST & WATER TIGHT TRANSFORMER 6,3KVA - IP65



SKU: TP AE656300\_Specific  
 Référence technique: A39B41...P.....

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 6,3 kVA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP65-IK08  
 Version : Transformer (specific)  
 Inrush current : less than or equal to 12 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 85 W  
 Load losses : 230 W  
 Voltage drop : 3,5 %  
 UCC : 3,8 %  
 Efficiency : 95,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 510 x 470 x 645 mm  
 Mounting centres (a x b) : 330 x 430 mm  
 Mounting diameter (ø) : 11x22 mm  
 Weight : 74 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Specific colour for the enclosure