



TP AE 65 80000 - TTHREE-PHASE DUST & WATER TIGHT TRANSFORMER 400/230V - 80KVA - IP65



SKU: 38525
 Référence technique: A39B52...P...FD00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 80 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP65-IK08
 Version : Transformer (specific)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 540 W
 Load losses : 1045 W
 Voltage drop : 1,3 %
 UCC : 2,7 %
 Efficiency : 98,1 %

DIMENSIONS:

Dimensions (A x B x H) : 900 x 790 x 1010 mm
 Mounting centres (a x b) : 570 x 750 mm
 Mounting diameter (Ø) : 11x22 mm
 Weight : 430 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 125A
 :
 Secondary 230V (gG fuse(s)) : 4 x 200A
 Secondary 230V (C circuit breaker(s)) : 4 x 200A

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure