



TPAP 10000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 10KVA - IP21



SKU: 34437

Référence technique: A38B43FDF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 10 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : Transformer (regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 120 W
Load losses : 575 W
Voltage drop : 5,4 %
UCC : 6 %
Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm
Mounting centres (a x b) : 330 x 340 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 70 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 230V (gG fuse(s)) : 4 x 25A
Secondary 230V (C circuit breaker(s)) : 4 x 25A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure