



TPAP 100000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 100KVA - IP21



SKU: 34536
 Référence technique: A38B53FD01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 100 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP21-IK08
 Version : with electrostatic shield
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 710 W
 Load losses : 2090 W
 Voltage drop : 2 %
 UCC : 3,5 %
 Efficiency : 97,3 %

DIMENSIONS:

Dimensions (A x B x H) : 800 x 520 x 980 mm
 Mounting centres (a x b) : 570 x 490 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 390 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 160A
 :
 Secondary 230V (gG fuse(s)) : 4 x 250A
 Secondary 230V (C circuit breaker(s)) : 4 x 250A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure