




TPAP 100000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 100KVA - IP21



SKU: 34538

Référence technique: A38B53FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 100 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : with electrostatic shield & regulation tabs $\pm 5\%$
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 710 W
Load losses : 2090 W
Voltage drop : 2 %
UCC : 3,5 %
Efficiency : 97,3 %

DIMENSIONS:

Dimensions (A x B x H) : 800 x 520 x 980 mm
Mounting centres (a x b) : 570 x 490 mm
Mounting diameter (\varnothing) : 11x22 mm
Weight : 390 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 160A
:
Secondary 230V (gG fuse(s)) : 4 x 250A
Secondary 230V (C circuit breaker(s)) : 4 x 250A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure