



TPAP 12500 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 12,5KVA - IP21



SKU: 33446
 Référence technique: A38B44FF01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 12,5 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP21-IK08
 Version : Transformer (regulation tabs $\pm 5\%$)
 Inrush current : less than or equal to $12 I_n$
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 125 W
 Load losses : 830 W
 Voltage drop : 6,2 %
 UCC : 6,7 %
 Efficiency : 92,9 %

DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm
 Mounting centres (a x b) : 330 x 340 mm
 Mounting diameter (\varnothing) : 11x22 mm
 Weight : 76 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 20A
 :
 Secondary 400V (gG fuse(s)) : 4 x 20A
 Secondary 400V (C circuit breaker(s)) : 4 x 20A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure