





## TPAP 125000 - THREE-PHASE TRANSFORMER 400/230V - 125KVA - IP21



SKU: 34545  
 Référence technique: S38B54FD00000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 125 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP21-IK08  
 Version : standard  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 800 W  
 Load losses : 2850 W  
 Voltage drop : 2,2 %  
 UCC : 4,7 %  
 Efficiency : 97,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 960 x 820 x 930 mm  
 Mounting centres (a x b) : 620 x 770 mm  
 Mounting diameter (Ø) : 14 mm  
 Weight : 485 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 315A  
 Secondary 230V (C circuit breaker(s)) : 4 x 315A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Runnig wheels  
 Factory assembled and wired primary and secondary protections  
 Specific colour for the enclosure