




## TPAP 16000 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 16KVA - IP21



SKU: 33456  
 Référence technique: A38B45FF01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 16 kVA  
 Primary voltage : 400V  
 Secondary voltage : 400V (Y+N)  
 :  
 Protection : IP21-IK08  
 Version : Transformer (regulation tabs  $\pm 5\%$ )  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 165 W  
 Load losses : 890 W  
 Voltage drop : 5,3 %  
 UCC : 5,9 %  
 Efficiency : 93,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm  
 Mounting centres (a x b) : 395 x 340 mm  
 Mounting diameter ( $\varnothing$ ) : 11x22 mm  
 Weight : 95 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 25A  
 :  
 Secondary 400V (gG fuse(s)) : 4 x 25A  
 Secondary 400V (C circuit breaker(s)) : 4 x 25A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Runnig wheels  
 Factory assembled and wired primary and secondary protections  
 Specific colour for the enclosure