



## TPAP 16000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 16KVA - IP21



SKU: 34457  
Référence technique: A38B45FDF0000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 16 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP21-IK08  
Version : Transformer (regulation tabs  $\pm 5\%$ )  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 165 W  
Load losses : 890 W  
Voltage drop : 5,3 %  
UCC : 5,9 %  
Efficiency : 93,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm  
Mounting centres (a x b) : 395 x 340 mm  
Mounting diameter ( $\varnothing$ ) : 11x22 mm  
Weight : 95 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 25A  
:  
Secondary 230V (gG fuse(s)) : 4 x 40A  
Secondary 230V (C circuit breaker(s)) : 4 x 40A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure