




## TPAP 200000 - THREE-PHASE TRANSFORMER 400/230V - 200KVA - IP21



SKU: 34565  
Référence technique: S38B56FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 200 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP21-IK08  
Version : standard  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1070 W  
Load losses : 3590 W  
Voltage drop : 1,8 %  
UCC : 4 %  
Efficiency : 97,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 1140 x 870 x 1060 mm  
Mounting centres (a x b) : 770 x 820 mm  
Mounting diameter (Ø) : 14 mm  
Weight : 667 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 315A  
:  
Secondary 230V (gG fuse(s)) : 4 x 500A  
Secondary 230V (C circuit breaker(s)) : 4 x 500A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure