





**TPAP 25000 - THREE-PHASE  
TRANSFORMER 400/400V ±5% -  
ELECTROSTATIC SHIELD - 25KVA - IP21**



SKU: 33478  
Référence technique: A38B47FFF1000

### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 25 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP21-IK08  
Version : Transformer (specific)  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 250 W  
Load losses : 1010 W  
Voltage drop : 3,9 %  
UCC : 4,4 %  
Efficiency : 95,2 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 580 x 370 x 600 mm  
Mounting centres (a x b) : 395 x 340 mm  
Mounting diameter (Ø) : 11x22 mm  
Weight : 124 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 40A  
:  
Secondary 400V (gG fuse(s)) : 4 x 40A  
Secondary 400V (C circuit breaker(s)) : 4 x 40A

### **OPTIONS:**

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure