




TPAP 250000 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 250KVA - IP21



SKU: 33576
 Référence technique: S38B57FF01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 250 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP21-IK08
 Version : with electrostatic shield
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 1360 W
 Load losses : 4520 W
 Voltage drop : 1,8 %
 UCC : 5 %
 Efficiency : 97,7 %

DIMENSIONS:

Dimensions (A x B x H) : 1200 x 970 x 1180 mm
 Mounting centres (a x b) : 820 x 920 mm
 Mounting diameter (Ø) : 14 mm
 Weight : 823 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 400A
 :
 Secondary 400V (gG fuse(s)) : 4 x 400A
 Secondary 400V (C circuit breaker(s)) : 4 x 400A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure