




TPAP 31500 - THREE-PHASE TRANSFORMER 400/400V ±5% - 31,5KVA - IP21



SKU: 33487
 Référence technique: A38B48FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 31,5 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP21-IK08
 Version : Transformer (electrostatic shield & regulation tabs ±5%)
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 285 W
 Load losses : 1265 W
 Voltage drop : 3,9 %
 UCC : 4,3 %
 Efficiency : 95,3 %

DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm
 Mounting centres (a x b) : 395 x 440 mm
 Mounting diameter (Ø) : 11x22 mm
 Weight : 158 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 50A
 :
 Secondary 400V (gG fuse(s)) : 4 x 50A
 Secondary 400V (C circuit breaker(s)) : 4 x 50A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure