




TPAP 315000 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 315KVA - IP21



SKU: 33586

Référence technique: S38B58FF01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 315 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP21-IK08
Version : with electrostatic shield
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 1500 W
Load losses : 5180 W
Voltage drop : 1,6 %
UCC : 4,7 %
Efficiency : 97,9 %

DIMENSIONS:

Dimensions (A x B x H) : 1200 x 970 x 1180 mm
Mounting centres (a x b) : 820 x 920 mm
Mounting diameter (∅) : 14 mm
Weight : 933 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 500A
:
Secondary 400V (gG fuse(s)) : 4 x 500A
Secondary 400V (C circuit breaker(s)) : 4 x 500A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure