



## TPAP 315000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 315KVA - IP21



SKU: 34586  
Référence technique: S38B58FD01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 315 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP21-IK08  
Version : with electrostatic shield  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1500 W  
Load losses : 5180 W  
Voltage drop : 1,6 %  
UCC : 4,7 %  
Efficiency : 97,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 1200 x 970 x 1180 mm  
Mounting centres (a x b) : 820 x 920 mm  
Mounting diameter (ø) : 14 mm  
Weight : 933 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 500A  
:  
Secondary 230V (gG fuse(s)) : 4 x 800A  
Secondary 230V (C circuit breaker(s)) : 4 x 800A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure