



TPAP 40000 - THREE-PHASE TRANSFORMER 400/230V - 40KVA - IP21



SKU: 34495
Référence technique: A38B49FD00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 40 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : Transformer (standard)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 335 W
Load losses : 1430 W
Voltage drop : 3,5 %
UCC : 4 %
Efficiency : 95,8 %

DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm
Mounting centres (a x b) : 395 x 440 mm
Mounting diameter (Ø) : 11x22 mm
Weight : 181 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 63A
:
Secondary 230V (gG fuse(s)) : 4 x 100A
Secondary 230V (C circuit breaker(s)) : 4 x 100A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure