



TPAP 400000 - THREE-PHASE TRANSFORMER 400/230V - 400KVA - IP21



SKU: 34595
 Référence technique: S38B59FD00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 400 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP21-IK08
 Version : Transformer (standard)
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 1700 W
 Load losses : 6180 W
 Voltage drop : 1,5 %
 UCC : 4,6 %
 Efficiency : 98,1 %

DIMENSIONS:

Dimensions (A x B x H) : 1350 x 1200 x 1350 mm
 Mounting centres (a x b) : 920 x 1150 mm
 Mounting diameter (Ø) : 14 mm
 Weight : 1185 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 630A
 :
 Secondary 230V (gG fuse(s)) : 4 x 1000A
 Secondary 230V (C circuit breaker(s)) : 4 x 1000A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure