



## TPAP 400000 - THREE-PHASE TRANSFORMER 400/230V ±5% - ELECTROSTATIC SHIELD - 400KVA - IP21



SKU: 34598  
 Référence technique: S38B59FDF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 400 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP21-IK08  
 Version : Transformer (electrostatic shield & regulation tabs ±5%)  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 1700 W  
 Load losses : 6180 W  
 Voltage drop : 1,5 %  
 UCC : 4,6 %  
 Efficiency : 98,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 1350 x 1200 x 1350 mm  
 Mounting centres (a x b) : 920 x 1150 mm  
 Mounting diameter (Ø) : 14 mm  
 Weight : 1185 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 630A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 1000A  
 Secondary 230V (C circuit breaker(s)) : 4 x 1000A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Runnig wheels  
 Factory assembled and wired primary and secondary protections  
 Specific colour for the enclosure