



## TPAP 5000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 5KVA - IP21



SKU: 33407  
Référence technique: T29B40FFF0000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 5 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP21-IK08  
Version : Transformer (regulation tabs  $\pm 5\%$ )  
Inrush current : less than or equal to 12 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 85 W  
Load losses : 210 W  
Voltage drop : 4 %  
UCC : 4,1 %  
Efficiency : 94,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm  
Mounting centres (a x b) : 250 x 340 mm  
Mounting diameter ( $\varnothing$ ) : 11x22 mm  
Weight : 50 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 400V (gG fuse(s)) : 4 x 8A  
Secondary 400V (C circuit breaker(s)) : 4 x 8A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure