



TPAP 50000 - THREE-PHASE TRANSFORMER 400/230V - 50KVA - IP21



SKU: 34505
 Référence technique: A38B50FD00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 50 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP21-IK08
 Version : Transformer (standard)
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 405 W
 Load losses : 1700 W
 Voltage drop : 3,3 %
 UCC : 4 %
 Efficiency : 96 %

DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm
 Mounting centres (a x b) : 395 x 440 mm
 Mounting diameter (Ø) : 11x22 mm
 Weight : 207 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 80A
 :
 Secondary 230V (gG fuse(s)) : 4 x 125A
 Secondary 230V (C circuit breaker(s)) : 4 x 125A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure