






TPAP 500000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 500KVA - IP21



SKU: 34606
Référence technique: S38B60FD01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 500 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : Transformer (electrostatic shield)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 1960 W
Load losses : 6400 W
Voltage drop : 1,3 %
UCC : 5 %
Efficiency : 98,4 %

DIMENSIONS:

Dimensions (A x B x H) : 1350 x 1200 x 1350 mm
Mounting centres (a x b) : 920 x 1150 mm
Mounting diameter (ø) : 14 mm
Weight : 1395 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 800A
:

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure