




TPAP 6300 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 6,3KVA - IP21



SKU: 33417
Référence technique: T29B41FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 6,3 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP21-IK08
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 95 W
Load losses : 300 W
Voltage drop : 4,5 %
UCC : 4,7 %
Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm
Mounting centres (a x b) : 330 x 340 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 60 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 20A
:
Secondary 400V (gG fuse(s)) : 4 x 10A
Secondary 400V (C circuit breaker(s)) : 4 x 10A

OPTIONS:

Tropicalization
Specific colour for the enclosure