



## TPAP 63000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 63KVA - IP21



SKU: 33517  
Référence technique: A38B51FFF0000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 63 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP21-IK08  
Version : with regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 485 W  
Load losses : 1840 W  
Voltage drop : 2,8 %  
UCC : 3,6 %  
Efficiency : 96,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 800 x 520 x 980 mm  
Mounting centres (a x b) : 470 x 490 mm  
Mounting diameter ( $\varnothing$ ) : 11x22 mm  
Weight : 248 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 100A  
:  
Secondary 400V (gG fuse(s)) : 4 x 100A  
Secondary 400V (C circuit breaker(s)) : 4 x 100A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure