




TPAP 630000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 630KVA - IP21



SKU: 33617
Référence technique: S38B61FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 630 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP21-IK08
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 2260 W
Load losses : 8690 W
Voltage drop : 1,4 %
UCC : 4,7 %
Efficiency : 98,3 %

DIMENSIONS:

Dimensions (A x B x H) : 1350 x 1200 x 1350 mm
Mounting centres (a x b) : 920 x 1150 mm
Mounting diameter (\varnothing) : 14 mm
Weight : 1590 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1000A
:

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure