





## TPEC 10000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/400V - 10KVA - IP00



SKU: 35431  
Référence technique: A66B43FF00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 10 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : Transformer (energy savings ECO DESIGN A0AK)  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 55 W  
Load losses : 530 W  
Voltage drop : 5 %  
UCC : 5,5 %  
Efficiency : 94,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 420 x 265 x 350 mm  
Mounting centres (a x b) : 330 x 235 mm  
Mounting diameter (∅) : 11 x 22 mm  
Weight : 58 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 400V (gG fuse(s)) : 4 x 16A  
Secondary 400V (C circuit breaker(s)) : 4 x 16A

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Vibration isolating mount  
Runnig wheels