




TPEC 100000 - ON REQUEST THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 100KVA - IP00



SKU: TPEC100000_Specific
 Référence technique: A66B53...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 100 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : économies d'énergie ECO DESIGN A0Ak (specific)
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 252 W
 Load losses : 1800 W
 Voltage drop : 1,8 %
 UCC : 2,4 %
 Efficiency : 98 %

DIMENSIONS:

Dimensions (A x B x H) : 670 x 420 x 620 mm
 Mounting centres (a x b) : 500 x 340 mm
 Mounting diameter (ø) : 14 mm
 Weight : 450 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels