




## TPEC 125000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/400V - 125KVA - IP00



SKU: 35541  
Référence technique: S66B54FF00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 125 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : économies d'énergie ECO DESIGN A0Ak  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 300 W  
Load losses : 2140 W  
Voltage drop : 1,7 %  
UCC : 3,6 %  
Efficiency : 98,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 780 x 480 x 620 mm  
Mounting centres (a x b) : 500 x 360 mm  
Mounting diameter (ø) : 14 mm  
Weight : 515 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A  
:  
Secondary 400V (gG fuse(s)) : 4 x 200A  
Secondary 400V (C circuit breaker(s)) : 4 x 200A

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Vibration isolating mount  
Runnig wheels