





## TPEC 31500 - ON REQUEST THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 31,5KVA - IP00



SKU: TPEC31500\_Specific  
 Référence technique: A66B48...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 31,5 kVA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP00  
 Version : Transformer (energy savings ECO DESIGN A0Ak - specific)  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 115 W  
 Load losses : 1270 W  
 Voltage drop : 3,9 %  
 UCC : 4,5 %  
 Efficiency : 95,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 490 x 370 x 530 mm  
 Mounting centres (a x b) : 395 x 340 mm  
 Mounting diameter (∅) : 11 x 22 mm  
 Weight : 147 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Vibration isolating mount  
 Running wheels