




TPECP 100000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/400V - 100KVA - IP21



SKU: 35535
 Référence technique: A67B53FF00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 100 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP21-IK08
 Version : économies d'énergie ECO DESIGN A0Ak
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 252 W
 Load losses : 1800 W
 Voltage drop : 1,8 %
 UCC : 2,4 %
 Efficiency : 98 %

DIMENSIONS:

Dimensions (A x B x H) : 960 x 820 x 930 mm
 Mounting centres (a x b) : 620 x 770 mm
 Mounting diameter (Ø) : 14 mm
 Weight : 510 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 160A
 :
 Secondary 400V (gG fuse(s)) : 4 x 160A
 Secondary 400V (C circuit breaker(s)) : 4 x 160A

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Rung wheels
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure