





## TPECP 12500 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/230V - 12,5KVA - IP21



SKU: 36445  
 Référence technique: A67B44FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 12,5 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP21-IK08  
 Version : Transformer (energy savings ECO DESIGN A0AK)  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 65 W  
 Load losses : 725 W  
 Voltage drop : 5,5 %  
 UCC : 2,9 %  
 Efficiency : 94,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm  
 Mounting centres (a x b) : 330 x 340 mm  
 Mounting diameter (Ø) : 11 x 22 mm  
 Weight : 78 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 20A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 32A  
 Secondary 230V (C circuit breaker(s)) : 4 x 32A

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Vibration isolating mount  
 Running wheels  
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure