





## TPECP 125000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/230V - 125KVA - IP21



SKU: 36545  
 Référence technique: S67B54FD00000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 125 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP21-IK08  
 Version : économies d'énergie ECO DESIGN A0Ak  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 300 W  
 Load losses : 2140 W  
 Voltage drop : 1,7 %  
 UCC : 3,6 %  
 Efficiency : 98,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 1140 x 870 x 1060 mm  
 Mounting centres (a x b) : 770 x 820 mm  
 Mounting diameter (Ø) : 14 mm  
 Weight : 587 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 315A  
 Secondary 230V (C circuit breaker(s)) : 4 x 315A

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Vibration isolating mount  
 Rung wheels  
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure