




TPECP 250000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/230V - 250KVA - IP21



SKU: 36575
Référence technique: S67B57FD00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 250 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : économies d'énergie ECO DESIGN A0Ak
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 470 W
Load losses : 3400 W
Voltage drop : 1,3 %
UCC : 4 %
Efficiency : 98,5 %

DIMENSIONS:

Dimensions (A x B x H) : 1200 x 970 x 1180 mm
Mounting centres (a x b) : 820 x 920 mm
Mounting diameter (Ø) : 14 mm
Weight : 968 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 400A
:
Secondary 230V (gG fuse(s)) : 4 x 630A
Secondary 230V (C circuit breaker(s)) : 4 x 630A

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections

Specific colour for the enclosure